



07-18 JEEP WRANGLER JK/JKU 18+ JEEP WRANGLER JL/JLU 20+ JEEP GLADIATOR

FOOT PEG INSTALLATION INSTRUCTIONS

JFP01

Thanks for purchasing a Reaper Off-Road foot peg set. Our team has worked to ensure that this product is the premium in performance, quality, and fitment. We are proud to say that this product will enhance the look and off-road performance of your vehicle. We encourage you to read through the following steps, and check the included Bill of Materials before beginning. Please follow these steps to ensure that your installation goes as planned.

Our products are specifically designed with ease of installation in mind. However, if you are uncomfortable with the following instructions please seek professional assistance. Reaper Off-Road will not be held liable for harm or injury to yourself or your vehicle during installation or use of this product.



Recommended Tool List



- Jeep door & hardtop toolkit

R1018
V01 - 7.16.21



Visit us online:
ReaperOffRoad.com

Call Us Toll-Free:
844-868-3022

 [reaper.off.road](https://www.instagram.com/reaper.off.road)
 [Reaper-Off-Road](https://www.facebook.com/Reaper-Off-Road)

ASSEMBLY

These steps are based on already having the doors removed. Follow manufacturers guidelines for door removal. Steps may vary depending on model year

07-18 WRANGLER JK/JKU
18+ WRANGLER JL/JLU
20+ GLADIATOR JT

FOOT PEG
PAGE 2

1. Install vinyl caps (D) onto footpeg studs to protect paint.
2. Position foot peg around door hinge.
3. Slide (2) plastic washers (B) between the peg and the door hinge to protect paint - (1) above the hinge and (1) below.
4. Assemble washer (B) and bolt (A) from above, through the bracket and hinge. Secure with another washer (B) and nut (C) from below.
5. Use the provided 7/32" hex bit (E) and your tool kit's ratchet, with a 9/16" wrench to tighten.
6. Repeat the same process for the other doors.



Detail 1: Caps installed



Detail 4: Hardware installed



Detail 5: Foot peg installed



Detail 6

R1018
V01 - 7.16.21